

**Waterproof  
ABS Wiegand  
card reader**



**PW2-E  
PW2-M  
PW2-DM**

**Mini small size  
wiegand card reader**

### Overview:

This new generation of small size ABS Wiegand card reader conforms to waterproof IP67. It supports EM 125KHz or Mifare 13.56MHz or EM&Mifare. The users can choose the Wiegand format by themselves with the remote controller. It can be easily integrated into other systems with the Wiegand output.

### Features:

- » **Power:** DC10-24V
- » **Input:** EM 125KHz | Mifare 13.56MHz | UID 4bytes,7bytes,Plus) | EM & Mifare | NFC213-216 | Mobile NFC
- » **Output:** Wiegand 26-44bit,47,56,58,64,66bit
- » **Dimension:** 83×42×18mm

## SPECIFICATIONS:

<b>Power</b>	Wide Range DC10-24V
<b>Input</b>	EM125KHz   Mifare 13.56MHz (UID 4bytes,7bytes Plus)   NFC 213-216   Mobile NFC
<b>Output</b>	Wiegand protocol EM 26-44bit   Mifare 26-44bit,56,58,64,66bit
<b>Mifare card type</b>	Mifare Plus, Mifare DesFire, Mifare Pro, Mifare UltraLight, Mifare Class, NFC213   216,S50,S70
<b>Environmental</b>	Temperature:-40°C~+70°C Humidity: 10%-98%RH
<b>Dimension &amp; Weight</b>	83×42×17mm 0.25kg
<b>Wiegand output format can be set</b>	Wiegand output for card: factory default is Wiegand 26(EM)/34(Mifare) The users can set the Wiegand format with any kind of external keypad reader which supports 4bit/8bit key output.
<b>Warranty</b>	Two years warranty