



PW6-EM  
PW6-EH  
PW6-M  
PW6-DM  
PW6-A

**Mini small size  
wiegand card reader**

### Overview:

This new generation of plastic ABS Rfid card reader conforms to waterproof IP67. It has thickened ABS housing which is classic and cost effective. It can be integrated into any other system with the Wiegand protocol output.

### Features:

- » **Power:** DC10-24V
- » **Input:** EM125KHz | Mifare 13.56MHz (UID 4bytes,7bytes Plus) | NFC 213-216 | Mobile NFC
- » **Output:** Wiegand protocol
- » **Dimension:** 100×43×20mm

## SPECIFICATIONS:

<b>Power</b>	Wide Range DC10-24V
<b>Input</b>	EM125KHz   Mifare 13.56MHz (UID 4bytes,7bytes Plus)   NFC 213-216   Mobile NFC
<b>Output</b>	Wiegand protocol
<b>Color</b>	Black & Gray
<b>Mifare card type</b>	Mifare Plus, Mifare DesFire, Mifare Pro, Mifare UltraLight, Mifare Class, NFC213   216,S50,S70
<b>Environmental</b>	Temperature:-40°C~+70°C Humidity: 10%-98%RH
<b>Dimension &amp; Weight</b>	100×43×20mm 0.3kg
<b>Wiegand output format can be set</b>	Wiegand output for card: factory default is Wiegand 26(EM)/34(Mifare) The users can set the Wiegand format with any kind of external keypad reader
<b>Warranty</b>	Two years warranty