



### PW-275 Series

PW275-DMC (Unmonitored Version)

PW275-DLMC (Monitored Version)

### 600lbs Double EMAG Lock

### Overview:

PW-275 series renders advance security monitoring by integrating door status monitoring function (DSMF) (providing door opened/closed signal) in addition to the standard lock status monitoring function (LSMF). MonAct™ series Monitored EM locks are inbuilt with magnetic contact were designed to meet fire and life safety applications by providing an auxiliary locking mechanism that has no moving parts to bind or wear out for trouble free operation. This will ensure inhibited release at all times where they have become extremely prevalent in applications other than fire/life safety. Suitable for higher security areas within buildings with double leaf doors.

### Features:



Life Safety Applications



Zero Residual Magnetism



Low Energy Consumption



Cost Savings



12/24Vdc Selectable



Door Status Monitoring

### Extended Features:

- » Lock Status Monitoring Function (LSMF)
- » Anodized Aluminium Housing
- » CE Compliance

## SPECIFICATIONS:

	PW275-DMC	PW-275-DLMC
<b>Holding Force</b>	Up to 600lbs x 2	
<b>Magnet Size</b>	500 X 42 X 26 mm	
<b>Armature Size</b>	80 X 38 X 11 mm	
<b>Current Drain</b>	480mA±10%/12Vdc 240mA±10%/24Vdc	
<b>Operating Temperature</b>	(-10 to 55)°C (14 to 131)°F	
<b>Housing Finishing</b>	Anodized Aluminium	
<b>Est. Weight</b>	3.71kg	

## WIRING DIAGRAM

